

SAFETY DATA SHEET

P-50016
EXI-264

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: #711 THINNER . Product Code: T711

SUPPLIER:

MICHIGAN COATING PRODUCTS

3761 EASTERN AVE SE

WYOMING MI 49508

PHONE 616-456-8800

EMERGENCY 24 HOURS 800-373-7542

MANUFACTURER:

MICHIGAN COATING PRODUCTS

3761 EASTERN AVE SE

WYOMING MI 49508

PHONE 616-456-8800

EMERGENCY HOURS 800-373-7542

SECTION 2 - HAZARDS IDENTIFICATION

NEPA Ratings, risks phrases and suggested HMIS Hazards Categories:

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Dermal Toxicity	Acute Tox. 3	Dermal>200+<=1000mg/kg
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	2	Human or animal evidence possibly with other information
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm ² /s at 40° C.

GHS Hazards

H225	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation.

GHS Precautions

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	KEEP AWAY FROM HEAT/sparks/open flames/hot surfaces -No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	WASH HANDS THOROUGHLY after handling.
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P280	WEAR PROTECTIVE GLOVES/protective clothing/eye protection/face protection.
P281	USE PERSONAL PROTECTIVE EQUIPMENT as required.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P330	Rinse mouth
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352	IF ON SKIN: Wash with soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	IN CASE OF FIRE: Use dry chemical (BC) or carbon dioxide (Co2) for extinction.
P405	Store locked up.
P403+P235	STORE IN A WELL VENTILATED PLACE. Keep cool.
P501	Dispose of contents/container in accordance with Local, State and Federal Regulations.

Signal Word: Danger



SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
2-Butoxyethanol	111-76-2	30.00% - 40.00%
Methyl propyl ketone	107-87-9	30.00% - 40.00%
Solvent naphtha, petroleum, light aromatic	64742-95-6	30.00% - 40.00%

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove to FRESH air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration, preferably mouth-to-mouth. GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Tilt head to avoid contaminating unaffected eye. Get immediate medical attention. Remove contact lenses if possible.

SKIN CONTACT: Flush skin with plenty of water while removing contaminated clothing and shoes. Do not reuse clothing or shoes until cleaned. If irritation develops or persists, get medical attention. Discard contaminated leather articles such as shoes and belt. Do not apply oils or ointments unless ordered by the physician.

INGESTION: If fully conscious, give two glasses of water, then induce vomiting by touching back of throat with finger. Keep head below hips to prevent aspiration of liquid into the lungs. CALL A PHYSICIAN immediately. Never induce vomiting or give anything by mouth to an unconscious victim.

NOTE TO PHYSICIANS: There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Individuals experiencing breathing difficulties after exposure to vapor generated in aerosol applications should be observed for at least 48 hours in case delayed respiratory complications develop.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 7 C (45 F)

LEL: 1.00

UEL:

Flammable Limits: Highly flammable liquid and vapor (GHS Category 2)

Extinguishing Media: Alcohol Foam CO2 Dry Chemical Foam Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Do not use when smoking or where electrical sparks or open flame is present.

Haz. Combust. Products: Burning can produce carbon-dioxide and/or carbon monoxide.

Fire Fighting: Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Fire Equipment: As in a fire, always wear self-contained breathing apparatus in pressure-demand (MSA/NIOSH approved or equivalent), and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES:

Spill supervisor: Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

Small Spills: Absorb spilled liquid with sorbent pads, socks, or other inert material such as vermiculite, sand, or earth.

Large Spills: Avoid run-off into storm sewers and ditches that lead to waterways. Use only non-sparking tools and equipment. A vapor suppressing foam may be used. Approach the spill from upwind and pick up absorbent material and place it in a suitable container. Disposal should be in accordance with Local, State, and Federal Regulations.

SECTION 7 - HANDLING AND STORAGE

HANDLING PRECAUTIONS:

Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: GROUNDING: when transferring, fill stem and container must be grounded and bonded. Store in a cool dry area with ventilation suitable for storing materials shown in section II. Keep away from heat, sparks and open flame. Do not cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
2-Butoxyethanol 111-76-2	50 ppm TWA; 240 mg/m3 TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m3 TWA
Methyl propyl ketone 107-87-9	200 ppm TWA; 700 mg/m3 TWA	150 ppm STEL	NIOSH: 150 ppm TWA; 530 mg/m3 TWA
Solvent naphtha, petroleum, light aromatic 64742-95-6	Not Established	Not Established	Not Established

ENGINEERING: Ensure processing (curing) ovens are properly vented to prevent the introduction of processing fumes into the work place. Use explosion proof equipment and good manufacturing practice.

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH'S TLV limit.

OTHER PRECAUTIONS: Provide respiratory protection against fumes generated during burning. Avoid prolonged contact with skin and breathing of vapors.

PROTECTIVE GEAR: NIOSH/OSHA approved respirator types suitable for materials in section II recommended. Approved airline type respirators or hoods recommended in confined areas. Wear protective gloves/clothing/eye/face as required.

CONTAMINATED GEAR: Take off immediately any contaminated clothing and wash it before reuse.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

This mixture typically exhibits the following properties under normal circumstances:

Appearance Liquid dispersion Vapor Pressure: N/A Vapor Density Heavier than air SG 0.86 Freezing point: Not Applicable Boiling range: 102°C Evaporation Rate Slower than ether Autoignition temperature: Not Applicable Viscosity: Not Applicable	Odor Solvent Odor threshold: Not Applicable pH: Not Applicable Melting point: Not Applicable Solubility: Not Applicable Flash point: 7°C, 45°F Physical State Liquid Decomposition temperature: Not Applicable Boiling Point 102°C
--	---

SECTION 10 - STABILITY AND REACTIVITY

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

No data found

This mixture is likely to exhibit the following combustion products:

No data found

Hazardous polymerization will not occur.

SECTION 11- TOXICOLOGICAL INFORMATION

Mixture Toxicity

Oral Toxicity LD50: 1,090mg/kg

Dermal Toxicity LD50: 660mg/kg

Inhalation Toxicity LC50: 1,192mg/L

Component Toxicity

111-76-2 2-Butoxyethanol

Oral LD50: 470 mg/kg (Rat) Dermal LD50: 220 mg/kg (Rabbit) Inhalation LC50: 450 ppm

107-87-9

Methyl propylketone

Oral LD50: 1,600 mg/kg (Rat)

64742-95-6

Solvent naphtha, petroleum, light aromatic

Inhalation LC50: 3,400 ppm(Rat)

Toxicological Information: No data found

ROUTES OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

Exposure to this material may affect the following organs:

Blood Eyes
System

Kidneys

Liver

Central Nervous System

Skin

Respiratory

Effects of Overexposure

Carcinogenicity:

The following chemicals comprise 0.1% or more of this mixture and are listed and / or classified as carcinogens or potential carcinogens by

NTP, IARC, OSHA.
CAS Number
None

Description

% Weight

Carcinogen Rating
N/A

SECTION 12 - ECOLOGICAL INFORMATION

Ecological information: No data found.

Component Ecotoxicity

2-Butoxyethanol

96 Hr LC50 *Lepomis macrochirus*: 1490 mg/L [static]; 96 Hr LC50 *Lepomis macrochirus*: 2950 mg/L

48 Hr EC50 *Daphnia magna*: >1000 mg/L

Methyl propyl ketone

96 Hr LC50 *Pimephales promelas*: 1190 - 1290 mg/L [flow-through]

Solvent naphtha, petroleum, light aromatic

96 Hr LC50 *Oncorhynchus mykiss*: 9.22 mg/L

48 Hr EC50 *Daphnia magna*: 6.14 mg/L

SECTION 13 - DISPOSAL CONSIDERATIONS

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. State and local disposal regulations may differ from federal disposal definitions found in 40 CFR 261.3. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 - TRANSPORT INFORMATION

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	UN1263, PAINT RELATED MATERIAL	1263	II	3
IATA	UN1263, PAINT RELATED MATERIAL	1263	II	3
IMDG	UN1263, PAINT RELATED MATERIAL	1263	II	3

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

This product contains the following substances subject to the reporting requirements of Section 313 of Title II of the Superfund Amendments and Reauthorization Act of 1986 and CFR Part 40

- None

Country

Regulation

All Components Listed

EU Risk Phrases

R10: Flammable

Safety Phrase

S16: Keep away from sources of ignition - No smoking


SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	2
PERSONAL PROTECTION	I

HMIS & NFPA Hazard Rating
Legend
 * = Chronic Health Hazard
 0 = INSIGNIFICANT
 1 = SLIGHT
 2 = MODERATE
 3 = HIGH



The information contained on this SDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

Reviewer Revision

Date Prepared: 6/14/2016