

P50526

MATERIAL SAFETY DATA SHEET

PAGE 1 OF 3
DATE PRINTED: 9/15/92

DATE OF LAST CHANGE: 10/06/92

DISTRIBUTOR'S NAME:

RECEIVED

MAY 31 2010

EMERGENCY TELEPHONE NO. 000-
INFORMATION TELEPHONE NO. 000-

SECTION 1 -- PRODUCT INFORMATION

TRADE NAME: GT SERIES PIGMENTS

PRODUCT CLASS:

PRODUCT GROUP: DIST

CD:GT
- H M I S C O D E S -
HEALTH - 1
FLAMMABILITY - 1
REACTIVITY - 0

PRODUCT	wt/gal lb	VOC g/l	VOC lb/gal	% VOC VOL	PRODUCT	wt/gal lb	VOC g/l	VOC lb/gal	% VOC VOL
30250RM	10.4	0	.0	0	39062RM	10.8	0	.0	0
31045RM	10.8	0	.0	0	39063RM	11.3	0	.0	0
31046RM	11.3	0	.0	0	39180RM	10.8	0	.0	0
32810RM	11.4	0	.0	0	39200RM	11.3	0	.0	0
33037RM	11.3	0	.0	0	39530RM	11.3	0	.0	0
33054RM	11.3	0	.0	0	39540RM	10.8	0	.0	0
39020RM	10.8	0	.0	0	33052RM	11.4	0	.0	0
33151RM	11.4	0	.0	0		.0	0	.0	0
	.0	0	.0	0		.0	0	.0	0

SECTION 2 -- HAZARDOUS INGREDIENTS

CHEMICAL NAME;
COMMON NAME;
CAS NUMBER

OCCUPATIONAL EXPOSURE LIMITS

VAPOR
PRESSURE
IN mmHg

TLV

PEL

PIGMENTS;
MIXTURE;
CAS #'s: NOT ESTABLISHED

10MG/M3

15MG/M3

N/A

(As DUST)

* BASIC RED 1
BASIC RED #1
CAS #: 989-38-8NOT
ESTABLISHEDNOT
ESTABLISHED

N/A

* SUBJECT TO REPORTING REQUIREMENT
OF SECTION 313 OF TITLE III OF
SARA (40 CFR PART 372)

SECTION 3 -- PHYSICAL DATA

BOILING RANGE: NOT APPLICABLE

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

SEE SECTION 1 FOR VOC DATA.
SEE SECTION 1 FOR WEIGHT PER GAL. DATA

SECTION 4 -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION:

OSHA CLASSIFICATION: Not Regulated DOT CLASSIFICATION: Not Regulated

OTHER COMMENTS:

NFPA RATING: H-1 F-1 R-0

FLASH POINT:

Not applicable.

LOWER EXPLOSIVE LEVEL:

Not applicable.

EXTINGUISHING MEDIA:

Foam- CO2- Dry Chemical- Water Spray.

USUAL FIRE AND EXPLOSION HAZARDS:

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Potential for dust explosion. Fumes released on burning are toxic and dangerous.

SPECIAL FIREFIGHTING PROCEDURES:

Water may be ineffective but may be used to cool containers. The use of self-contained breathing apparatus is recommended for fire fighters.

Potential for dust explosion. Fumes released on burning are toxic and dangerous.

SECTION 5 -- HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

Eye contact may cause slight irritation. May cause irritation to skin. Inhalation may cause respiratory tract irritation. WARNING: THIS PRODUCT CONTAINS <0.1% FORMALDEHYDE, A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

MEDICAL CONDITIONS PRONE TO AGGRAVATE BY EXPOSURE:

Persons with pre-existing skin or lung disorders may be more susceptible to the effects of this material. Repeated and prolonged overexposure and/or individual sensitivity may increase the potential for and degree of adverse health effects.

PRIMARY ROUTE(S) OF ENTRY:

Inhalation

EMERGENCY AND FIRST AID PROCEDURES:

SKIN CONTACT: Wash with soap and water, contact physician if irritation persists. EYE CONTACT: Flush well with running water for a minimum of 15 minutes, contact physician if irritation persists. INHALATION: Remove to fresh air, restore breathing, contact physician. INGESTION: Contact physician or Poison Control Center immediately.

OTHER COMMENTS:

The potential health effects of this product are based on the hazards of

OTHER COMMENTS:

its components. TSCA Inventory: All ingredients listed.

SECTION 6 -- REACTIVITY DATA

STABILITY:

Stable.

CONDITIONS TO AVOID:

Heat, sparks and open flame.

INCOMPATIBILITY (WITH MATERIALS):

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide, Carbon Dioxide and other noxious gases.

HAZARDOUS POLYMERIZATION:

Will not occur.

SECTION 7 -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

This product is not defined as a hazardous waste under EPA 40 CFR 261. Sweep up and dispose of as any dust or dirt. Use non-sparking tools to place material in appropriate container for disposal.

WASTE DISPOSAL METHOD:

Same as above.

SECTION 8 -- SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

If particulate concentration exceeds the TLV listed in Section II, use NIOSH approved respirator with particulate. Contact a reputable safety supply company for the appropriate respirator.

VENTILATION:

Use applicable engineering controls, work practices, and personal protective equipment to keep the vapor concentration below the TLV listed in Section 11. This product is capable of outgassing formaldehyde in quantities exceeding 1PPM. If this occurs increase ventilation.

PROTECTIVE GLOVES:

Contact a reputable safety supply company for appropriate gloves if irritation occurs.

EYE PROTECTION:

Use splash-proof goggles or safety glasses. Contact a reputable safety supply company for appropriate eye protection.

OTHER PROTECTION:

Smoke in designated areas only. Availability of an eye wash is recommended.

HYGIENIC PRACTICES:

Wash with soap and water before eating, smoking or using toilet facilities. Remove contaminated clothing to prevent prolonged skin contact.

SECTION 9 -- SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Store in closed containers in cool, dry, well ventilated area away from sources of ignition. Keep containers closed when not in use.

OTHER PRECAUTIONS:

Avoid prolonged or repeated overexposure to this product. Empty containers should be disposed of in an environmentally safe manner in accordance with applicable regulations.

SECTION 10 -- DISCLOSURE

DISCLOSURE INFORMATION:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind express or implied is made with respect to the information contained herein.
