

INSULATED PLATFORMS

- Work platforms are designed for maximum safety and ease of installation
- Permanent non-slip surface in the work area
- Metal castings and components on platforms are made from heat-treated aluminum alloys
- Platforms have square channel foot/toe stops for location awareness
- Platform width is 10 3/4"
- Twin struts for stability
- Pivot Assembly comes complete with chain tighteners
- Struts fold for storage
- The rail assembly hinges and stores on top of the platform by removing the keeper pin
- The horizontal rail assembly is a positioning device that will allow the worker to maintain proper work positioning and balance
- Not to be used as an anchor point - see anchor point tool page 316
- Platform can be positioned in 30 degree increments up to 180 degrees under load by loosening wheel tightener. No need to get off the board to reposition



CAT NO	DESCRIPTION	LOAD LIMIT	LBS
8401	4' PLATFORM WITH RAIL AND PIVOT ASSEMBLY	500 LBS	93
8402	6' PLATFORM WITH RAIL AND PIVOT ASSEMBLY	500 LBS	111
8403	8' PLATFORM WITH RAIL AND PIVOT ASSEMBLY	500 LBS	129
8404	10' PLATFORM WITH RAIL AND PIVOT ASSEMBLY	500 LBS	147

**PLATFORMS INCLUDE THE RAIL AND PIVOT ASSEMBLIES
AND WILL NOT BE SOLD IN ANY OTHER CONFIGURATION**