




3501 3502 3503

WOOD BLOCKS

- Wood blocks have 4" bronze bushed sheaves with loose swivel hooks, safety snaps, and becket for attaching rope

CAT NO	DESCRIPTION	UPPER	LOWER	LBS
3501	BLOCK ONLY - NO ROPE	1 SHEAVE		2.4
3502	BLOCK ONLY - NO ROPE	2 SHEAVES		3.5
3503	BLOCK ONLY - NO ROPE	3 SHEAVES		5.0
3504	BLOCKS WITH 125' OF 1/2" POLYPROPYLENE ROPE	2 SHEAVES	2 SHEAVES	12.5
3505	BLOCKS WITH 150' OF 1/2" POLYPROPYLENE ROPE	3 SHEAVES	2 SHEAVES	16.0
3506	BLOCKS WITH 150' OF 1/2" POLYPROPYLENE ROPE	3 SHEAVES	3 SHEAVES	17.0

*OTHER LENGTHS AND STYLES OF ROPE AVAILABLE UPON REQUEST.

**WORKING LOAD LIMIT - SINGLE - 1000 LBS, DOUBLE - 1400 LBS, TRIPLE - 1800 LBS. (SEE PAGE 802)



3510

HEAVY DUTY STEEL BLOCK

- 8" sheave steel block
- For wire rope and winch line applications
- Swivel type hook assembly includes safety latch that is pinned
- Accepts up to 3/4" rope
- Threaded pin with keeper allows for access to sheave assembly
- Working load limit 16,000 lbs/8 ton (See Page 802)

CAT NO	DESCRIPTION	LBS
3510	BLOCK ONLY	30



3535

3518

3533

SELF LOCKING DOUBLE SHEAVE BLOCKS

- Light duty metal tackle blocks with drop forged snap hooks, oilite bearings and aluminum sheaves, designed for use with 3/8" rope
- Not for human lifting
- Working load limit 750 lbs. (See Page 802)

CAT NO	DESCRIPTION	LBS
3515	BLOCKS WITH 25' OF 3/8" MANILA ROPE - NON-SWIVEL HOOK	3.5
3534	BLOCKS WITH 25' OF 3/8" MANILA ROPE - SWIVEL HOOK	3.5
3516	BLOCKS WITH 25' OF 3/8" NYLON ROPE - NON-SWIVEL HOOK	3.5
3535	BLOCKS WITH 25' OF 3/8" NYLON ROPE - SWIVEL HOOK	3.5
3517	BLOCKS ONLY WITH NON-SWIVEL HOOK	2.0
3536	BLOCKS ONLY WITH SWIVEL HOOK	2.0
3518	NON-SWIVEL HOOK ONLY	0.4
3533	SWIVEL HOOK ONLY	0.4

*OTHER LENGTHS AND STYLES OF ROPE AVAILABLE UPON REQUEST.